3M[™] Adhesive Transfer Tape Double Linered 7955MP, Transparent, 610 mm x 914 mm, 0.13 mm



- Use with graphic and nameplate attachments, giving a smooth appearance on graphic overlays
- Resist moisture, UV, solvent and high temperatures
- Prevent mess by being easy to die-cut and apply
- Use with graphic and nameplate attachments, giving a smooth appearance on graphic overlays
- Resist moisture, UV, solvent and high temperatures
- Prevent mess by being easy to die-cut and apply

Specifications

* Smallest Saleable Unit ?

Details

Adhesive Type	High Performance Acrylic Adhesive 200MP
Applications	Bonding
Brand	ЗМ™
Maximum Operating Temperature (Celsius)	204 Degree Celsius
Overall Length (Metric)	914 mm
Overall Width (Metric)	610 mm
Primary Liner	58# Polycoated Kraft Paper
Primary Liner Color	Tan

3M[™] Adhesive Transfer Tape Double Linered 7955MP, Transparent, 610 mm x 914 mm, 0.13 mm

Primary Liner Thickness (Metric)	0.11 mm
Secondary Liner	58# Polycoated Kraft Paper
Secondary Liner Color	Tan
Secondary Liner Thickness (Metric)	0.11 mm
Shelf Life	547 Days
Smallest Saleable Unit	Case
Smallest Saleable Unit*	Case
Total Tape Thickness without Liner (metric)	0.13 mm

Dimensions and Classifications

Case Gross Weight*	28.009 Kilogram
Case Height*	68 Millimeter
Case Length*	948 Millimeter
Case Volume*	41.257 Cubic decimeter
Case Width*	640 Millimeter
Pallet Gross Weight	293.786 Kilogram
Pallet Height	830 Millimeter
Pallet Length	1,200 Millimeter
Pallet Volume	796.8 Cubic decimeter
Pallet Width	800 Millimeter
ECCN Number	
Harmonizing code	3506919099

Packaging and Identifications

Country of Origin	Poland
Country of Origin Disclaimer	This is to advise you that as of this date, the Country of Origin for the product(s) displayed is as follows. This origin is for purposes of Normal Trade Relations (NTR) duty treatment, is for import/export documentation only, and is not intended to be used for any other purpose such as sales to government entities or Free Trade Agreement eligibility. Government procurement laws and Free Trade Agreements require application of specific criteria that may result in a different Country of Origin than indicated. These determinations are specific to 3M ID.
EAN/GTIN - Pallet (Pallet)	05900422040309
EAN/GTIN – Shipper (Case)*	05900422039907
Primary Shipping Location	JUECHEN, Nordrhein-Westfalen

3M[™] Adhesive Transfer Tape Double Linered 7955MP, Transparent, 610 mm x 914 mm, 0.13 mm

	Primary Shipping Location Disclaimer	The Primary Shipping Location may not be the final source of the product
	per Pallet	10 Case
Tr	ansportation	
	Air Shipping Available	Yes

No

Details

Dry Ice Shipping Required

- Use with graphic and nameplate attachments, giving a smooth appearance on graphic overlays
- Resist moisture, UV, solvent and high temperatures
- Prevent mess by being easy to die-cut and apply
- Use with graphic and nameplate attachments, giving a smooth appearance on graphic overlays
- Resist moisture, UV, solvent and high temperatures
- Prevent mess by being easy to die-cut and apply

Prevent mess with easy to die-cut and apply 3M[™] Adhesive Transfer Tape Double Linered 7955MP. Our tape is ideal for graphic and nameplate attachment, giving a smooth appearance on graphic overlays. It offers excellent moisture, UV, solvent and high temperature resistance.

Get 3M[™] Adhesive Transfer Tape Double Linered 7955MP to use with graphic and nameplate attachments, giving a smooth appearance on graphic overlays, whilst offering excellent moisture, UV, solvent and high temperature resistance. Our tape prevents mess by being easy to die-cut and apply. It's made with a high performance acrylic adhesive on double liner of polycoated kraft paper.

Resources

Bulletins

Laminating Adh - The Effect of Ink Drying on Bond Performance (PDF,11.4KB) Lamination Techniques for Converters of Laminating Adhesives (PDF,218.6KB) Ford WSS-M11P62 - Tested 3M Tapes (PDF,198.5KB) 3M GMW 14892 Automotive Spec (PDF,363.4KB) Nissan M8506 Technical Bulletin 2020 (PDF,605.0KB) 3M WSS-M99P48-A3 Automotive Spec (PDF,221.7KB) Microsoft Word - Ford Specification WSS-M11P62.pdf (PDF,564.0KB) Chrysler Specification MS-CC240 (PDF,137.8KB)

Data Sheets

<u>3M™ High Performance Acrylic Adhesive 200MP Transfer Tapes, TDS, Multilingual</u> (PDF, 3.5MB)

Technical Papers

9/20/23, 9:24 AM 3M[™] Adhesive Transfer Tape Double Linered 7955MP, Transparent, 610 mm x 914 mm, 0.13 mm

Shelf Life Technical Bulletin (PDF,160.4KB)