


## 3M™ Scotchcal™ Graphic Film 3690 B, White, 910 mm x 250 m



Make To Order

- Printable in screen printing (offset printing is not recommended)
- Stretchable
- Suitable for severe weather and handling conditions encountered by commercial and industrial graphics including labels, emblems and striping and small format original equipment manufacturer's (OEM) decorative and identification graphics, cautionary, safety and vandal-resistant labeling.

## Specifications

\* Smallest Saleable Unit ?

### Details

|                                  |  |
|----------------------------------|--|
| <b>Adhesive Features</b>         | Pressure-sensitive                         |
| <b>Adhesive Type</b>             | Solvent Acrylic                            |
| <b>Application Surface</b>       | Simple Curve                               |
| <b>Brand</b>                     | Scotchcal™                                 |
| <b>Color Palette</b>             | White                                      |
| <b>Converting Process</b>        | Screenprinting                             |
| <b>Factory ISO Certification</b> | No ISO Certification information available |
| <b>Film Thickness (Metric)</b>   | 50 Micrometre (Micron)                     |
| <b>Film Type</b>                 | Cast                                       |
| <b>Imaging Method</b>            | UV Screenprint<br>Solvent Screenprint      |

|  |                                  |
|--|----------------------------------|
| <b>Maximum Service Temperature (Celsius)</b>     | 90 Degree Celsius                |
| <b>Minimum Application Temperature (Celsius)</b> | 4 Degree Celsius                 |
| <b>Minimum Service Temperature (Celsius)</b>     | -50 Degree Celsius               |
| <b>Opacity</b>                                   | Opaque                           |
| <b>Overall Length (Metric)</b>                   | 250 m                            |
| <b>Overall Width (Metric)</b>                    | 910 mm                           |
| <b>Product Code</b>                              | 3690 B                           |
| <b>Product Color</b>                             | White                            |
| <b>Product Usage</b>                             | Buildings                        |
| <b>Removability</b>                              | Removable with Heat              |
| <b>Service Life</b>                              | 7 Year                           |
| <b>Shelf Life</b>                                | 1095 Days                        |
| <b>Smallest Saleable Unit*</b>                   | Case                             |
| <b>Substrates</b>                                | Sand Cast<br>Low Energy Surfaces |
| <b>Surface Finish</b>                            | Glossy                           |

## Dimensions and Classifications

|                            |                         |
|----------------------------|-------------------------|
| <b>Case Gross Weight*</b>  | 61.318 Kilogram         |
| <b>Case Height*</b>        | 536 Millimeter          |
| <b>Case Length*</b>        | 1,140 Millimeter        |
| <b>Case Volume*</b>        | 256.637 Cubic decimeter |
| <b>Case Width*</b>         | 420 Millimeter          |
| <b>Pallet Gross Weight</b> | 147.635 Kilogram        |
| <b>Pallet Height</b>       | 690 Millimeter          |
| <b>Pallet Length</b>       | 1,200 Millimeter        |
| <b>Pallet Volume</b>       | 695.52 Cubic decimeter  |
| <b>Pallet Width</b>        | 840 Millimeter          |
| <b>ECCN Number</b>         |                         |
| <b>Harmonizing code</b>    | 3919908099              |

## Packaging and Identifications

|                                     |   |
|-------------------------------------|---|
| <b>Country of Origin</b>            | Germany   |
| <b>Country of Origin Disclaimer</b> | This is to advise you that as of this date, the Country of Origin for the product(s) displayed is as follows. This origin is for purposes of Normal Trade Relations (NTR) duty treatment, is for import/export documentation only, and is not intended to be used for any other purpose such as |

sales to government entities or Free Trade Agreement eligibility. Government procurement laws and Free Trade Agreements require application of specific criteria that may result in a different Country of Origin than indicated. These determinations are specific to 3M ID.

|   |  |
|---|--|
| <b>EAN/GTIN - Pallet (Pallet)</b>           | 04054596517011   |
| <b>EAN/GTIN – Shipper (Case)*</b>           | 04054596507920   |
| <b>Primary Shipping Location</b>            | Hilden, Nordrhein-Westfalen  |
| <b>Primary Shipping Location Disclaimer</b> | The Primary Shipping Location may not be the final source of the product |
| <b>per Case*</b>                            | 1 Roll   |
| <b>per Pallet</b>                           | 2 Roll   |

## Transportation

|                                  |     |
|----------------------------------|-----|
| <b>Air Shipping Available</b>    | Yes |
| <b>Dry Ice Shipping Required</b> | No  |

## Details

- Printable in screen printing (offset printing is not recommended)
- Stretchable
- Suitable for severe weather and handling conditions encountered by commercial and industrial graphics including labels, emblems and striping and small format original equipment manufacturer's (OEM) decorative and identification graphics, cautionary, safety and vandal-resistant labeling.

A white, premium cast opaque film (50 µm) with a permanent, grey pigmented, extremely aggressive, pressure sensitive adhesive for applications requiring good adhesion to sand cast and moderately rough surfaces. Suitable for flat surfaces and simple curves. Up to 7 years durability.