## 

## **Providing Solutions in Pressure Sensitive Films**

## **Product Construction Sheet**

FLEXmark® PM 500 WHITE TC-249 L-23 (1.45) 50K6

GENERAL DESCRIPTION:

This is a topcoated printable white polyester film coated with a permanent pressure sensitive acrylic adhesive and backed with a kraft roll label liner.

UL RECOGNITION:

This product is UL recognized for indoor/outdoor use with occasional exposure to lubricating oil and water. For further information, please reference FLEXcon's UL file No MH10170 (N) or contact your FLEXcon Representative.

PRODUCT DATA	VALUE	TEST METHOD
PHYSICAL PROPERTIES		
Thickness	Film: 125 +/- 10 %	ASTM D 3652
(micron)	Adhesive: 36 -38 +/- 3 Liner: 75 +/- 10 %	
Dimensional Stability (%)	No shrinkage observed	On Al panel at 70°C for 24 hr.
ADHESION PROPERTIES**		
Adhesion from (N/m)	Average	
Stainless Steel	726	FTM 1 (Modified for
Acrylic	737	72 hr dwell time)
Glass	682	
Expected Shear (hours)	25	FTM 8
Tack (gm/sq cm)	370	ASTM D 2979
<pre>** For guidance only This data is based on limited test results due to the custom nature of this product, not to be used for setting specifications.</pre>		
EXPECTED EXTERIOR LIFE	Two year	
SERVICE TEMPERATURE RANGE	-40°C to 150°C	
MINIMUM APPLICATION TEMPERATURE		
STORAGE STABILITY	Two years stored at 21`C and 50% RH	
* FLEXmark is a registered trader	mark of FLEXcon Company, Inc.	20.05.2009.

## **Product Performance and Suitability**

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.