



# High Temperature Resistant Labelstock 3922

## Product Data Sheet

Updated : December 2010

**Description :** High temperature resistant labelstock 3922. is recommended for thermal transfer imaged labelstock applications where a high durability and superb resistance against highest application temperature is required.

The acrylic based film is resistant to outdoor weathering, UV-light and many solvents aswell as being dimensionally stable.

The matte white facestock provides a very good contrast which leads to a high first readability rate; even of high density BARCODES.

Lower adhesive coat weight and siliconised liner to facilitate excellent conversion and dispensing whilst maintaining excellent adhesion properties.

### Physical Properties

Not for specification purposes  
(Calipers are nominal values)

Facestock	50 µm White matte cast acrylic film
Adhesive	20 µm # 150 Crosslinked acrylate adhesive
Liner	56 micron, 62 g/m <sup>2</sup> White Densified Glassine
Shelf Life	24 months from date of manufacture by 3M when properly stored at 22°C & 50 % Relative Humidity

### Physical Properties

Not for specification purposes

Minimum Application Temperature	+15°C
Elongation	5% - 15%
Tensile Strength	> 30N/25mm (Test conditions: DIN50014 on tensile tester according to DIN51221/DIN51220; 300mm/min, 100mm Film length)
Dimensional Stability (DIN30646)	< 0.2 %

### Environmental Performance

Not for specification purposes

Weather Resistance	Accelerated weathering in Zenon Tester 1,000 hr : No Change To Film
Temperature Resistance	*300°C (60 sec)      No change *200°C (60 min)      No change *80°C (14 days)      No change  A slight yellow tinge may occur after times listed. The temperatures have no impact on the form stability of the film. <b>Low Temperature Resistance</b> -40°C (7 days) No change
Weather Resistance	Accelerated weathering in Xenon tester (in accordance with DIN 30646) 2000 hours : No Change No Change to Film

**Adhesion**

FINAT FTM 2  
 72 hrs dwell time, 300mm/min.  
 Pullback 90° Angle.

Substrate	N/10mm
PCB solder mask	2.5
Afera Steel	5.4
Aluminium	6.7
ABS	7.2
PP	3.0
PVC	4.0
PC	5.0

The adhesion on Printed Circuit Boards is depending on the used lacquer system. (Test conditions in accordance with FINAT FTM 2, 72 hours dwell time, 300mm / min Pull Back, 90° angle).

**Chemical & Solvent Resistance**

Film applied onto PCB panels 1 hour prior to immersion and evaluated directly after the test. Duration of immersion, 10 minutes at room temperature.

Xylo	No change
n-Heptane	No change
Ethanol	No change
Isopropanol	No change
Water	No change
Sulphuric Acid (30%)	No change
Caustic Soda (10%)	No change
Trichloroethane 1,1,1	No change
Toluene (5 minutes)	No change

\* The film is not resistant to harsh fluorine-chlorine.

<b>Abrasion Resistance</b>	Grinding wheel: CS10 Load : 500g 1000 cycles no surface damage
----------------------------	--

<b>Processing</b>	<p><b>Printing:</b>          High temperature resistant labelstock 3922. is recommended for screenprinting processes using appropriate inks from suppliers like Wiederhold, Marabu etc. Both UV and solvent-based inks are suitable. Sheet screenprinting must be evaluated depending on size and actual conditions. Flexographic, letterpress and offset printing methods can be considered but should be evaluated on a case to case basis.</p> <p><b>Cutting:</b>          High temperature resistant smooth, hard, caliper controlled liner with very good kiss cutting characteristics. Weed stripping is recommended using a 25 mm idler. For better handling we recommend label formats with "rounded" corners.</p> <p><b>Application:</b>          All surfaces must be clean and dry and at ambient temperature of over 10°C. High temperature resistant labelstock 3922. has been developed for application to smooth surfaces.</p> <p><b>Storage:</b>          Unprocessed films: at least two years and Processed labels: one year.          Films and labels must be stored in a clean area free of excessive moisture and direct sunlight of room temperature. Processed labels should be stored in Polyethylene bags, 0.1 mm thickness, to protect against moisture fluctuations.</p>
-------------------	--

**Processing Contd....**

**Thermal Transfer:**

High temperature labelstock 3922 offers an ideal surface for Thermal **Imageability**.

**Transfer Printing.**

This technology provides excellent covering power combined with the capability of uniform surface coverage. It also allows the individual printing of high density BARCODES beyond standard labelling applications.

The quality of the printing is dependent on the printer/ribbon combination. Good results have been obtained with the following ribbons:

- Armor AXR 7+
- ICS- CC-4099-1
- Ricoh B.110 C
- Ricoh B.110 CX
- Ricoh B.110 A
- Sony 4070
- Sony 5070
- Japan Pulp and Paper JP Resin 1

**U.L file MH18072**

**Parameters:**

New printer/ribbon combinations should be evaluated beginning with lowest printing speed and highest burn temperature. Printing speed and burn temperature can be then successively increased/reduced.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

**Tapes & Adhesives Group**

3M United Kingdom PLC 2004

3M United Kingdom PLC 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT Product Information : Tel 0870 60 800 50 Fax 0870 60 700 99	3M Ireland 3M House, Adelphi Centre, Upper Georges Street, Dun Laoghaire, Co. Dublin, Ireland Customer Service : Tel (01) 280 3555 Fax (01) 280 3509
---	---

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



3M United Kingdom PLC  
 3M Centre, Cain Road,  
 Bracknell, Berkshire,  
 RG12 8HT

Product Information :  
 Tel 0870 60 800 50  
 Fax 0870 60 700 99

3M Ireland  
 3M House, Adelphi Centre,  
 Upper Georges Street,  
 Dun Laoghaire, Co. Dublin,  
 Ireland

Customer Service :  
 Tel (01) 280 3555  
 Fax (01) 280 3509

