

UPM Raflatac Technical Information

26.11.2009 ENG 351

SELF-ADHESIVE	ROLLS
FACE	RAFLACOAT PLUS
Gloss Coated	TS (sales code)
Product	White woodfree machine coated midgloss paper.
Use	Universal label paper for quality multicolour labels requiring high contrast and fine printing detail.

Typical technical values

Substance	80	g/m ²	ISO 536	
Caliper	70	µm	ISO 534	
Tensile strength MD	5.8	kN/m	ISO 1924/1	
Tensile strength CD	2.8	kN/m	ISO 1924/1	
Brightness	90	%	ISO 2470/1	
Roughness	1.0	microns	ISO 8791	PPS 10
Opacity	89	%	ISO 2471	
Gloss	64	%	Hunter 75°	
CIE Whiteness	120	%	ISO 11475	
Stiffness MD	0.23	mNm	ISO/DP 2493	
Stiffness CD	0.13	mNm	ISO/DP 2493	
Printability	Flexography, letterpress, offset, rotogravure and screen. Hot foil. Suitable for thermal transfer printing with wax/resin ribbons. Testing recommended.			
Advantages	This new medium stiffness paper is stronger and more rigid than ever providing faster conversion speeds. Provides high degree of print contrast and high opacity.			
Warranty	Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.			

This publication replaces all previous versions. All information is subject to change without notice.



UPM

www.upmraflatac.com